


23 1183 11178

MANNED MANEUVERING UNIT

Fran Bergonz
Martin Marietta


ORIGINAL PAGE
BLACK AND WHITE PHOTOGRAPH

MMU CAPABILITIES




ORIGINAL PAGE IS
OF POOR QUALITY

Manned Maneuvering Unit and Flight Support Station Details



ORIGINAL PAGE IS
OF POOR QUALITY

MMU/FSS INSTALLATION LOCATION




MMU PROPELLANT USAGE

- TANKS CHARGED WITH 26.2 POUNDS GN₂ FOR LAUNCH.
- AVAILABLE IMPULSE = 1593 LB-SEC.
- V = 66 FPS AT SYSTEM WEIGHT OF 755 LBS.
- AN ON-ORBIT RECHARGE PROVIDES UP TO 22.4 LBS GN₂.
- 1593 LB-SEC IMPULSE = 234 SEC OF TRANSLATIONAL COMMANDS
(4 THRUSTERS FIRING)
OR 468 SEC OF ROTATIONAL COMMANDS
(2 THRUSTERS FIRING)
- ASSUMING 75% TRANSLATION, 25% ROTATION, A SINGLE CHARGE PROVIDES
267 SECONDS OF THRUST.
- FOR 300 MILLISECOND COMMANDS (SOS FLIGHT SIMULATIONS AVERAGE)
THERE ARE 890 SEPARATE COMMANDS PER CHARGE.

ORIGINAL PAGE 13
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY


NUMBER OF ROUNDTrips VERSUS VELOCITY AND DISTANCE



* Assumes EVA crewmember does not depart from straightline path connecting the two endpoints by more than 3 feet.

MARTIN MARIETTA

MMU DELTA V CAPABILITIES WITH LARGE CARGOES




ORIGINAL PAGE IS
OF POOR QUALITY

MARTIN MARIETTA

ROTATIONAL MANEUVERS WITH LARGE CARGOES

RATE (DEG/S)	INERTIA (SLUG FT ²)	MOVEMENT ARM (FT)	REQUIRED IMPULSE (LB-SEC)	PERCENT FUEL USED
5	1,000	5	17.4	1.1
5	5,000	5	87.2	5.5
5	10,000	5	174.4	10.9
5	1,000	10	8.7	0.5
5	5,000	10	43.6	2.7
5	10,000	10	87.2	5.5
5	1,000	20	4.4	0.3
5	5,000	20	21.8	1.4
5	10,000	20	43.5	2.7
1	1,000	5	3.5	0.2
1	5,000	5	17.5	1.1
1	10,000	5	35.1	2.2
1	1,000	10	1.8	0.1
1	5,000	10	8.8	0.5
1	10,000	10	17.5	1.1
1	1,000	20	0.9	0.06
1	5,000	20	4.5	0.3
1	10,000	20	9.0	0.6

$$\text{IMPULSE} = \frac{\text{RATE (RAD/S)} \times \text{INERTIA}}{\text{MOMENT ARM}}$$



A 7181 POUND CYLINDRICAL SATELLITE, DIAMETER 12 FEET, HEIGHT 20 FEET, ATTACHED TO THE MMU AS SHOWN WOULD RESULT IN A SYSTEM INERTIA OF 10,000 SLUG FT² IN THE MMU PITCH AXIS. THE IMPULSE REQUIRED TO INITIATE A 1 DEG/SEC ROTATION RATE IS 17.5 LB-SEC OR 1.1% OF THE USABLE PROPELLANT LOAD.

MARTIN MARIETTA

ANCILLARY EQUIPMENT ATTACHMENT INTERFACE

- BALL FITTINGS ON INSIDE END OF CONTROL ARMS.
- MATING PART IS "TRAILER HITCH" TYPE LATCH.
- ATTACHMENT MADE BY PULLING LATCH ASSEMBLIES OVER BALL FITTINGS.
- DISENGAGED BY SIMPLE HAND LEVERS, EACH SIDE.

SATELLITE ATTACHMENT DEVICE

- ATTACHES TO MMU AT CONTROL ARM BALL FITTINGS.
- HARD CONTACT WITH SPACECRAFT TRUNNION FITTING CAUSES SPRING LOADED PADS TO GRASP EXTERIOR OF FITTING WHILE SIMULTANEOUSLY SENDING THREADED INSERT INTO INTERIOR OF FITTING.
- CREWMEMBER TURNS RATCHET HANDLE TO EXPAND INSERT TO FIT SNUGLY AGAINST INSIDE OF FITTING.
- AFTER SPACECRAFT RATES HAVE BEEN NULLED, MMU IS DISENGAGED FROM TRUNNION, LEAVING RMS GRAPPLE FIXTURE.
- SHUTTLE RMS ATTACHES TO GRAPPLE FIXTURE FOR SPACECRAFT BERTHING IN THE CARGO BAY.

SMALL PAYLOAD MANEUVERING SYSTEM (SPMS)

- o SMALL FREE FLIER BERTHED IN PAYLOAD BAY, CONTROLLED FROM AFT CREW STATION.
 - o SUPPORTS SHUTTLE PROXIMITY PAYLOAD SERVICE OPERATIONS.
 - o CAN BE LAUNCHED WITH PAYLOADS UP TO 800 POUNDS.
 - o SYSTEM CHARACTERISTICS.
 - TV/TELEMETRY - MTV BASELINE
 - COLD GAS (GN2) PROPELLANT
 - ΔV - WITHOUT PAYLOAD, 340 FT/SEC
 - WITH 800 LB PAYLOAD, 140 FT/SEC
 - OPERATING RANGE - 10 MILES
- CAN PROVIDE COMMAND, DATA, POWER, AND/OR PROPELLANT INTERFACES TO PAYLOAD
PROVIDES QUICK REACTION CAPABILITY FOR SMALL PAYLOADS

ORIGINAL PAGE IS
OF POOR QUALITY

MARTIN MARIETTA

ORIGINAL PAGE
BLACK AND WHITE PHOTOGRAPH

SPMS APPLICATIONS

